

XP-002147985

AN - 1977-18994Y [11]

CPY - NIMI

DC - E36 J01

FS - CPI

IC - B01D0/00 ; B01F0/00

MC - E31-F01 J01-E02A2 J02-A02

M3 - [01] C800 C730 C108 C216 C803 C802 C805 C804 C801 C550 N050 N160 Q431

M720 M411 M417 M424 M902

PA - (NIMI ) NIPPON LIGHT METAL CO

PN - JP52014577 A 19770203 DW197711 000pp

PR - JP19750090039 19750725

XIC - B01D-000/00 ; B01F-000/00

AB - J52014577 The device comprises a tank, a rotary shaft disposed in the centre of the tank, rotary plates mounted on the shaft, a perforated plate skirt mounted on the side edge of each plate, baffle plates disposed vertically in the tank, and an air feed pipe opened at the open side of the skirts.

- The tank is filled with a  $\text{Na}_2\text{SO}_3$  liq., the shaft is rotated to make turbulent the liq. by the effect of the baffle plates, while air is fed into the tank to contact with the liq.

IW - GAS LIQUID LIQUID LIQUID CONTACT DEVICE AIR OXIDATION SODIUM SULPHITE PURIFICATION SULPHUR

IKW - GAS LIQUID LIQUID LIQUID CONTACT DEVICE AIR OXIDATION SODIUM SULPHITE PURIFICATION SULPHUR

NC - 001

OPD - 1975-07-25

ORD - 1977-02-03

PAW - (NIMI ) NIPPON LIGHT METAL CO

TI - Gas-liquid or liquid-liquid contacting device - used for the air oxidn. of sodium sulphite in the purificn. of sulphur dioxide